

## SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

Revision: 09.01.2023

**CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml**

Page 1 of 11

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name

CIBUM PURA-TORQUE FG-HD 400ml

Product no.

PURTHD-A40

Unique formula identifier (UFI)

WXQF-R46F-K00Y-YKDY

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lubricant

Uses advised against

None known.

#### 1.3. Details of the supplier of the safety data sheet

Company and address

##### **CIBUM LUBRICANTS**

Stokagervej 5

8240 Risskov

Denmark

+45 3698 1899

[www.cibum-lubricants.com](http://www.cibum-lubricants.com)

E-mail

[mail@jim-tec.dk](mailto:mail@jim-tec.dk)

Revision

09/01/2023

SDS Version

1.0

#### 1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2; H315, Causes skin irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.

Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Causes skin irritation. (H315)

May cause drowsiness or dizziness. (H336)

Toxic to aquatic life with long lasting effects. (H411)

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

## CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml

Revision: 09.01.2023

Page 2 of 11

### Safety statement(s)

#### General

Keep out of reach of children. (P102)

#### Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not spray on an open flame or other ignition source. (P211)

Do not pierce or burn, even after use. (P251)

Wash hands and exposed skin thoroughly after handling. (P264)

Use only outdoors or in a well-ventilated area. (P271)

#### Response

Collect spillage. (P391)

#### Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

#### Disposal

Dispose of contents/container to an approved waste disposal plant. (P501)

### Hazardous substances

Naphtha (petroleum), light alkylate;Low boiling point modified naphtha;[A complex combination of hydrocarbons produced by distillation of the reaction products of isobutane with monoolefinic hydrocarbons usually ranging in carbon numbers from C3 through C5. It consists of predominantly branched chain saturated hydrocarbons having carbon numbers predominantly in the range of C7 through C10 and boiling in the range of approximately 90°C to 160°C (194°F to 320°F).]

### Additional labelling

Not applicable.

### 2.3. Other hazards

#### Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB. This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Naphtha (petroleum), light alkylate;Low boiling point modified naphtha;[A complex combination of hydrocarbons produced by distillation of the reaction products of isobutane with monoolefinic hydrocarbons usually ranging in carbon numbers from C3 through C5. It consists of predominantly branched chain saturated hydrocarbons having carbon numbers	CAS No.: 64741-66-8 EC No.: 265-068-8 UK-REACH: Index No.: 649-276-00-X	25-40%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

Revision: 09.01.2023

## CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml

Page 3 of 11

predominantly in the range of C7 through C10 and boiling in the range of approximately 90°C to 160°C (194°F to 320°F).]

Propane	CAS No.: 74-98-6	10-15%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	[16]
	EC No.: 200-827-9			
	UK-REACH:			
	Index No.: 601-003-00-5			

Butane (containing < 0,1 % butadiene (203-450-8))	CAS No.: 106-97-8	5-10%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	[16]
	EC No.: 203-448-7			
	UK-REACH:			
	Index No.: 601-004-01-8			

Isobutane (containing < 0,1 % butadiene (203-450-8))	CAS No.: 75-28-5	3-5%	Flam. Gas 1A, H220	
	EC No.: 200-857-2			
	UK-REACH:			
	Index No.: 601-004-01-8			

-----

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[16] Propel

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

#### General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

#### Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

#### Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

#### Eye contact

Upon irritation of the eye: Remove contact lenses and open eyes widely. Flush eyes with water or saline water(20-30°C) for at least 5 minutes. Seek medical assistance and continue flushing during transport.

#### Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

#### Burns

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

## CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml

Revision: 09.01.2023

Page 4 of 11

Rinse with water until pain stops then continue to rinse for 30 minutes.

#### 4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.  
Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Call a POISON CENTER/doctor if you feel unwell.

#### Information to medics

Bring this safety data sheet or the label from this product.

## SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

#### 5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO<sub>2</sub>)

#### 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: None

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Avoid direct contact with spilled substances.

Avoid inhalation of vapours from spilled material.

#### 6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

#### 6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.

Use sand, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations.

Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

#### 6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

## SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

#### 7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

Revision: 09.01.2023

## CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml

Page 5 of 11

escape and holds back packs flying around.

Recommended storage material

Keep only in original packaging.

Storage temperature

Aerosols: Do not expose to direct sunlight or temperatures above 50 ° C.

Do not expose to heat, hot surfaces, sparks, open flames or other sources of ignition. Smoking forbidden.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

## SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Butane (containing < 0,1 % butadiene (203-450-8))

Long term exposure limit (8 hours) (ppm): 600

Long term exposure limit (8 hours) (mg/m<sup>3</sup>): 1450

Short term exposure limit (15 minutes) (ppm): 750

Short term exposure limit (15 minutes) (mg/m<sup>3</sup>): 1810

Annotations:

Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

No data available.

PNEC

No data available.

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Provide adequate general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Work situation	Type	Class	Colour	Standards
In case of inadequate ventilation	Combination filter A2P2	Class 2	Brown/White	EN14387



# SAFETY DATA SHEET


Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

## CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml


Revision: 09.01.2023

Page 6 of 11


### Skin protection

Work situation	Recommended	Type/Category	Standards	
In the event of prolonged exposure or high concentrations	Dedicated work clothing should be worn.	-	-	

### Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
Nitrile	-	-	EN374-2	

### Eye protection

Work situation	Type	Standards	
When there is risk of formation of mist/aerosol	Safety glasses	EN166	

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Physical state

Aerosol

#### Colour

White

#### Odour / Odour threshold

Characteristic

#### pH

Testing not relevant or not possible due to the nature of the product.

#### Density (g/cm<sup>3</sup>)

Testing not relevant or not possible due to the nature of the product.

#### Kinematic viscosity

Testing not relevant or not possible due to the nature of the product.

#### Particle characteristics

Testing not relevant or not possible due to the nature of the product.

#### Phase changes

##### Melting point/Freezing point (°C)

Testing not relevant or not possible due to the nature of the product.

##### Softening point/range (waxes and pastes) (°C)

Does not apply to aerosols.

##### Boiling point (°C)

Testing not relevant or not possible due to the nature of the product.

##### Vapour pressure

Testing not relevant or not possible due to the nature of the product.

##### Relative vapour density

Testing not relevant or not possible due to the nature of the product.

##### Decomposition temperature (°C)

Testing not relevant or not possible due to the nature of the product.

#### Data on fire and explosion hazards

##### Flash point (°C)

Not applicable - product is an aerosol

##### Ignition (°C)

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

Revision: 09.01.2023

**CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml**

Page 7 of 11

Testing not relevant or not possible due to the nature of the product.

Auto flammability (°C)

Testing not relevant or not possible due to the nature of the product.

Lower and upper explosion limit (% v/v)

Testing not relevant or not possible due to the nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to the nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to the nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to the nature of the product.

9.2. Other information

Other physical and chemical parameters

No data available.

## SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

## SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

Revision: 09.01.2023

## CIBUM CLIBANO FG, Aerosol 400 ml

Page 8 of 11

### Aspiration hazard

Based on available data, the classification criteria are not met.

### 11.2 Information on other hazards

#### Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.  
Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

#### Endocrine disrupting properties

None known.

#### Other information

None known.

## SECTION 12: Ecological information

### 12.1. Toxicity

No data available.

### 12.2. Persistence and degradability

No data available.

### 12.3. Bioaccumulative potential

No data available.

### 12.4. Mobility in soil

No data available.

### 12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

### 12.6. Endocrine disrupting properties

None known.

### 12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 14 – Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

#### EWC code

Not applicable.

#### Specific labelling

Not applicable.

#### Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

## SECTION 14: Transport information

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F	-	Yes	Limited quantities: 1 L Tunnel restriction

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

## CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml

Revision: 09.01.2023

Page 9 of 11

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
					code: (D) See below for additional information.
IMDG UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F	-	Yes	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
					
IATA UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F	-	Yes	See below for additional information.
					

\* Packing group

\*\* Environmental hazards

### Additional information

Although this product is environmentally hazardous, the environmentally hazardous substance mark has been omitted as the product is supplied in packaging with a maximum quantity of 5 L / 5 kg.

ADR / See Table A, Section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

Hazchem Code: None

### 14.6. Special precautions for user

Not applicable.

### 14.7. Maritime transport in bulk according to IMO instruments

No data available.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Restrictions for application

Restricted to professional users.

People under the age of 18 shall not be exposed to this product.

#### Demands for specific education

No specific requirements.

#### SEVESO - Categories / dangerous substances

P3b - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 5.000 tonnes (net) / (upper-tier): 50.000 tonnes (net)

E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

#### Additional information

Not applicable.

#### Sources

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

Revision: 09.01.2023

**CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml**

Page 10 of 11

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment  
No

## SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

- H220, Extremely flammable gas.
- H225, Highly flammable liquid and vapour.
- H280, Contains gas under pressure; may explode if heated.
- H304, May be fatal if swallowed and enters airways.
- H315, Causes skin irritation.
- H336, May cause drowsiness or dizziness.
- H411, Toxic to aquatic life with long lasting effects.

Abbreviations and acronyms

- ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway
- ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ATE = Acute Toxicity Estimate
- BCF = Bioconcentration Factor
- CAS = Chemical Abstracts Service
- CE = Conformité Européenne
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- CSA = Chemical Safety Assessment
- CSR = Chemical Safety Report
- DMEL = Derived Minimal Effect Level
- DNEL = Derived No Effect Level
- EINECS = European Inventory of Existing Commercial chemical Substances
- ES = Exposure Scenario
- EUH statement = CLP-specific Hazard statement
- EWC = European Waste Catalogue
- GHS = Globally Harmonized System of Classification and Labelling of Chemicals
- IARC = International Agency for Research on Cancer (IARC)
- IATA = International Air Transport Association
- IBC = Intermediate Bulk Container
- IMDG = International Maritime Dangerous Goods
- LogPow = logarithm of the octanol/water partition coefficient
- MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
- OECD = Organisation for Economic Co-operation and Development
- PBT = Persistent, Bioaccumulative and Toxic
- PNEC = Predicted No Effect Concentration
- RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
- RRN = REACH Registration Number
- SCL = A specific concentration limit
- SVHC = Substances of Very High Concern
- STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
- STOT-SE = Specific Target Organ Toxicity - Single Exposure
- TWA = Time weighted average
- UN = United Nations
- UVBC = Unknown or variable composition, complex reaction products or of biological materials
- VOC = Volatile Organic Compound
- vPvB = Very Persistent and Very Bioaccumulative

# SAFETY DATA SHEET

Compiled in accordance with REACH Regulation (EC) No 1907/2006,  
as retained and amended in UK law

Revision: 09.01.2023

**CIBUM PURA-TORQUE FG-HD, Aerosol 400 ml**

Page 11 of 11

## Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.